



NOTE:

1. PRINTING: AWM 80°C 30V VW-1 YSB3.0 Super Speed Cable
2. RoHS compliant.
3. Operating Temperature: -15°C-80°C

ITEM NO	LENGHT
K5237.1	1000±30mm
K5237.1,8	1800±50mm
K5237.3	3000±70mm
K5237.5	5000±70mm

P1	P2
1	RED
2	WHITE
3	GREEN
4	BLACK
5	YELLOW
6	BLUE
7	DRAIN
8	DRAIN
9	ORANGE
	PURPLE
	BRAID+DRAIN
	SHELL

NO.	MAT. NAME	DESCRIPTION	Q' TY
④	CABLE	USB 3.0 28AWG (7/0.127TC*IP+E+WAM)*2+ (7/0.127TC*IP)+ (7/0.127TC*2C) +ABB E=0.127TC AL-MG JACKET:PVC/BLACK OD: .5.3±0.2mm	1 Pcs
③	OUTER MOLD	PVC 88A BLACK	2 Pcs
②	CONNECTOR	USB3.0 AF TYPE, The Pin Gold Plating, The Shell Nickel Plating, BLUE INSULATOR	1 Pcs
①	CONNECTOR	USB3.0 AM TYPE, The Pin Gold Plating, The Shell Nickel Plating, BLUE INSULATOR	1Pcs