


WIRING TYPE B Cross

1	12	Blue
2	11	Orange
3	10	Green
4	9	Brown
5	8	Gray
6	7	White
7	6	Red
8	5	Black
9	4	Yellow
10	3	Violet
11	2	Pink
12	1	Aqua



ITEM NO.	Length
S216785	0.5M
S216786	1M
S216787	2M
S216788	3M
S216789	5M
S216790	7.5M
S216791	10M
S216792	15M

⚠ Fiber Transfer Distance

	Wavelength	50/125 OM4
1 Gigabit Ethernet	850nm	1100m
10 Gigabit Ethernet	850nm	550m
40 Gigabit Ethernet	850nm	150m
100 Gigabit Ethernet	850nm	125m

Note:

- RoHS 2011/65/EU and amendment directives (EU) 2015/863 compliant; REACH 1907/2006/EC compliant.
- Operating Temperature: 0° C ~ +60° C
- Storage Temperature: -20° C ~ +70° C
- Min. bending radius : 10*D (Static) 20*D (Dynamic)
D: diameter of cable

Type	Multi-Mode
	MTP® ELITE LOW INSERTION LOSS
Insertion Loss	≤ 0.35dB (IEC 61300-3-4)
Return Loss	≥ 30dB (IEC 61300-3-6)
Test Wavelength	850nm

SinglePack: 1pc/SYNERGY21 A bag/test report+label;
SubPack: no; Carton +labelx2;

MATERIAL LIST:

⑥	FIBER OPTICAL CABLE 12C OM4 50/125 Round Jacket LSZH Erika violet OD: 3.0mm	L	
⑤	MTP® Black Boot	2	
④	Housing Erika violet USconec	2	
③	Plastic Body Black USconec	2	
②	Resin Ferrule PC MM USconec MTP® ELITE	2	
①	MTP® Black Dust cover	2	

NO	SPECIFICATION STANDARD	QT'Y	REMARK
----	------------------------	------	--------

SYNERGY 21

					CUSTOMER		ITEM NO.	see the chart		
Tan	Fan	Add the table about Transmission distance ⚠	2024-12-11	A1	PRODUCT NAME	MTP® ELITE F/F 12 Core OM4 Patch Cord	manufacture country:	CHINA	UNIT	mm
		NEW	2021-08-23	A0	DRAWNBY	CHECKBY	APPOBY	DATE		
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.	SYNERGY 21	SYNERGY 21	SYNERGY 21	2021-08-23		