



Note:
 1.RoHS 2.0 & Reach Compliant
 2.Text:

Test Grade Designation:Each to Reference		
Grade	IL/RL	Standard
Insertion Loss (IL)	≤0.3dB	IEC 61300-3-4
Return Loss (RL)	≥30dB	IEC 61300-3-6
Test Wavelength	850nm	
End face inspection	×400	

3. Operating Temperature: -40° C ~ +85° C
 4. Storage Temperature: -20° C ~ +70° C
 5. Min. bending radius : 10*D (Static) 20*D (Dynamic)
 D: diameter of cable

⑫	SC Duplex Connector Erika violet RAL4003	2pcs	
⑪	SC Clip Erika violet RAL4003	1pcs	
⑩	SC Dust Cap	2pcs	
⑨	SC/UPC MM Ferrule	2pcs	
⑧	Ring 1 2	4pcs	
⑦	Black Heat Shrink Tube	2pcs	
⑥	LC Clip Erika violet RAL4003	1pcs	
⑤	LC Dust Cap White	2pcs	
④	LC Duplex Connector Erika violet RAL4003	2pcs	
③	Flex-Angle boot ID: 2.0mm	4pcs	
②	LC/UPC MM Ferrule 126-128um	2pcs	
①	Fiber Optical Cable Duplex φ2.0mm OM4 50/125um Erika violet RAL4003 LSZH	L+0.1m	
NO.	SPECIFICATION STANDARD	QT' Y	REMARK

SYNERGY 21					
CUSTOMER				ITEM NO.	see the chart
PRODUCT NAME	Flex-Angle boot Patch Cords Duplex OM4 SC/UPC - LC/UPC	Manufacture country	CHINA	UNIT	MM
DRAWNBY	CHECKBY	APPOBY	DATE		
SYNERGY 21	SYNERGY 21	SYNERGY 21	2021-11-08		

		NEW	2021-11-08	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

