


>>> [Go to the shop article](#)



EAN CODE



High Performance Multimedia Player with Android 9.0. This player is ideal for playing digital content and is state-of-the-art.

CPU:	Amlogic S922X with 12nm 1.8G HZ, Quad core ARM Cortex-A73 - 1.7Ghz and dual core ARM Cortex-A53 CPU - 1.8Ghz
GPU:	ARM MaliTM-G52 MP6(6ppc)
Operating system:	Android 9.0
RAM:	2GB LPDDR4 (4Gb optional for OEM orders)
Storage capacity(flash memory):	16GB EMMC(8GB/32Gb/64Gb optional for OEM orders)
WIFI:	AP6398S 2.4G+5G the wireless module complies with IEEE 802.11 a/b/g/n/ac 2x2 MIMO standard and it can achieve up to a speed of 867Mbps with dual stream in 802.11n to connect the wireless LAN.
Bluetooth:	Bluetooth 5.0
Network:	1000M Ethernet Integrated IEEE 802.3 10/100/1000M Ethernet MAC with RGMII interface, Wake on Lan function supported.
WOL	Wake On Lan
SPDIF	YES
CEC	support



RTC	support
HDR	support
AV decode:	Audio:MP3,WAV,WMA,MPEG,PCM,AC3 etc.
Video/Picture	VP9 Profile-2 up to 4Kx2K@60fps H.265 HEVC MP-10@L5.1 up to 4Kx2K@60fps AVS2-P2 Profile up to 4Kx2K@60fps H.264 AVC HP@L5.1 up to 4Kx2K@30fps H.264 MVC up to 1080P@60fps MPEG-4 ASP@L5 up to 1080P@60fps (ISO-14496) WMV/VC-1 SP/MP/AP up to 1080P@60fps AVS-P16(AVS+) /AVS-P2 JiZhun Profile up to 1080P@60fps MPEG-2 MP/HL up to 1080P@60fps (ISO-13818) MPEG-1 MP/HL up to 1080P@60fps (ISO-11172) RealVideo 8/9/10 up to 1080P@60fps Multiple language and multiple format sub-title video support MJPEG and JPEG unlimited pixel resolution decoding (ISO/IEC-10918) Supports JPEG thumbnail, scaling, rotation and transition effects Supports *.mkv,*.wmv,*.mpg, *.mpeg, *.dat, *.avi, *.mov, *.iso, *.mp4, *.rm and *.jpg file formats Video/Picture Encoding Independent JPEG and H.265/H.264 encoder with configurable performance/bit-rate JPEG image encoding H.265/H.264 video encoding up to 1080P@60fps with low latency
Video Output	Built-in HDMI 2.1 transmitter including both controller and PHY with CEC, Dynamic HDR and HDCP 2.2, 4Kx2K@60 max resolution output o CVBS 480i/576i standard definition output o Supports all standard SD/HD/FHD video output formats: 480i/p, 576i/p, 720p, 1080i/p and 4Kx2K
External storage:	USB HOST 3.0*1 USB HOST 2.0*3
HDMI:	HDMI 2.1 Type-A 4Kx2K@60fps max resolution
AV output:	AUX+CVBS 480i/576i
Key output:	Power



Part No.: 188877
Vendor Part No.: AM6-S922X

Antenna:	2 Extra Antennas
Port:	TF Card x1
POWER INPUT:	DC 12V/2A
Dimension	11.6*11.6*2.8CM

Accessories

Part No.	Name
159452	ALLNET LTE Module Quectel EC25 Cat4 Mini PCIe
105571	ALLNET spare power supply 12V/2,0A
210354	ALLNET PoE Splitter-Mini/Extractor / Gigabit / 24W / 5V/12V Switchable / ALL-PS102G-AF-AT
214123	ALLNET Air Mouse G10 Pro Remote Control 2.4GHz USB Dongle with Infrared