



NOTES:

ELECTRICAL:

1. VOLTAGE RATING : 125V AC RMS
2. CURRENT RATING : 1.5A mp
3. CONTACT RESISTANCE : 100 MILLI OHMS MAX
4. INSULATION RESISTANCE : 1000M OHMS MIN @ 500V DC
5. DIELECTRIC STRENGTH : 750V AC RMS 60Hz, 1MIN
6. CAT. 6A PERMANENT LINK : CONFORM TO ANSI/TIA/EIA-568 B.2-1 ENVIRONMENTAL:

ENVIRONMENTAL:

1. STORAGE : -40° TO+85°
2. OPERATION : 0° TO+70°

RJ45 JACK COMPLY TO REQUIREMENTS OF IEC-60603-7-5 MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68 MECHANICAL

1. RJ45 JACK LIFE: 750 TIMES MIN
2. IDN LIFE : 200 TIMES MIN

PACKING: 1pcs/PE BAG + INNER CARTON

Accessory:

1. Cable Tie (75X1.9mm) X 8Pcs
 2. Instruction Sheet
 3. expanded screw X 2 Set
- Rohs2.0 COMPLAINT

ITEM NO.	Colour	Logo
S216314	Gray RAL 7035	SYNERGY 21 pantone black T 1 pantone blue 298C

MATERIAL LIST:

⑦	Upper Panel Cover	1.2mm thickness Metallic Panel with plastic powder cladding	1	
⑥	Bottom Panel :	1.5mm thickness Metallic Panel with plastic powder cladding	1	
⑤	RJ45 Jack :	Housing-Fireproof PBT UL-94V0 Pin-8P8C 3u" gold plated	8	
④	PCB	1.6mm UL 94V0	1	
③	IDC BODY	Fireproof PC/ABS UL-94V0/With Colour Coded Printing T568A/B	8	
②	IDC PIN	Phosphor Bronze & Tinned	64	
①	IDC TERMINAL	For 22-24 AWG Cable	8	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK

UPDATE LOGO AND COMPLIANT

NEW

2013-10-21

2013-10-08

A1

A

SYNERGY 21			
CUSTOMER	ITEM NO.	SEE THE CHART	
PRODUCT NAME	CAT. 6A MINI 8PORT SFP PATCH PANEL	MANUFACTURE COUNTRY:	CHINA
DRAWNBY	CHECKBY	APPROBY	DATE
SYNERGY 21	SYNERGY 21	SYNERGY 21	2013-10-08

BY CHK

REVISION RECORD MODIFICATIONS

DATE

REV.

SYNERGY 21

SYNERGY 21

SYNERGY 21

2013-10-08