

Datenblatt Art. 333.815

Data sheet | Fiche technique | Scheda tecnica | Fișa tehnică

19" Steckdosenleiste 1HE VM

Elektrische Kenngrößen		Electrical parameters	
Nennstrom / Bemessungsspannung	16A / 250V~	Rated current / rated voltage	16A / 250V~
Frequenz	50 Hz	Frequency	50 Hz
Netzanschluss		Power supply	
Zuleitung	2,0m H05VV-F 3G1,5mm ²	Supply cable	2,0m H05VV-F 3G1,5mm ²
Farbe Zuleitung	schwarz	Colour supply cable	black
Stecker	IEC60320 C20	Plug	IEC60320 C20
Stromausgang		Power output	
Steckdosen		Socket outlets	
8x IEC60320 C19		8x IEC60320 C19	
2-polig mit Schutzkontakt		2-pole with earthing contact	
Schwarz, ähnlich RAL 9005, 90°		Black, similar to RAL 9005, 90°	
16A 250V~, IP20		16A 250V~, IP20	
Weitere Produkteigenschaften		Further product attributes	
Abmessungen	437x44x47mm	Dimensions	437x44x47mm
Plattform	1 HE	Plattform	1 HE
Profil	VM	Profile	VM
Material		Material	
Gehäuse:		Housing:	
Aluminium, eloxiert		Aluminium, anodised	
Abdeckung:		Cover:	
PA6 GF30 850°C, schwarz ähnlich RAL 9005		PA6 GF30 850°C, black similar to RAL 9005	
Lieferumfang		Scope of delivery	
1x Steckdosenleiste ALU 1HE 19" VM		1x Power strip Alu 1U VM	
2x 19" Befestigungswinkel (lose beigelegt)		2x 19" mounting brackets (enclosed separately)	
Im Polybeutel		Packed in polybag	
Umgebungsbedingungen		Environmental conditions	
Schutzart	IP20	Protection type	IP20

