



Remark:

- 1.100% Open/Short Test
- 2.Contact Resistance: 30mOhm MAX.
- 3.Insulation Resistance:10M Ohm MIN.
- 4.HI-POT:DC 300VDC/10ms.
- 5.The product is RoHS compliant.
- 6.100% on-board test (the resolution of host to display extended test is 3840x2160 @ 60Hz)

Item NO.	Length(m)
K5561HQSW.1	1.0m
K5561HQSW.2	2.0m
K5561HQSW.3	3.0m
K5561HQSW.5	5.0m

ERP NO.:	SAMPLE DWG NO.:
DOC No.:	REVISION A0
CUSTOMER:	UNIT mm
CUSTOMER P/N:	SCALE NO
DESCRIPTION	PAGE NO 1/1
APPROVAL	DATE 2021/05/20
	DRAWN

ITEM	DESCRIPTIONS & SPECIFICATIONS	QTY	REMARK
⑦	External Mold SR,45P PVC, Black	1PC	
⑥	Shell Front / rear shells. ABS,Black	1SETS	
⑤	HDMI / PCBA HDMI A Male,Gold-Plated, 4μ~6μ. CHIP:PS176	1PC	
④	Shell Top/bottom shell. ABS,Black	1SETS	
③	Internal Mold Inner Mould PE		
②	Connector DP male head hook, Gold-Plated,4μ~6μ	1PC	
①	Cable DP Cable (7/0.10TS*1P+D/0.254+AL+MY)*5+ 7/0.10TS*5C+D/0.254+96/0.12AL,OD:6.0mm, Black PVC		

TOLERANCES UNLESS OTHERWISE STATED  
 X .# ±.1  
 X .# ±.02  
 XX .# ±.01